

PXB23308

Thermal Barcode Printer

Key features

- Various label width, can be 20mm-58mm
- Label paper auto detection
- Temperature control function
- Modularity design and meet with various applications
- Lables tear off automatically
- Support PDF417,QR CODE, Data matrix 2D Printing



Specifications

Model	PXB23308
Printing method	Direct thermal
Resolution	203dpi
Printing width	20-58mm
Printing speed	127mm/s. (Max.); 50.8mm/s. (Min.)
Print head temperature sensor	Thermal sensitive resistance
Print head position sensor	Micro switch
Media type	Paper roll, sticker, label fold, etc.
Bar code	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14
QR CODE	PDF417、QR CODE、Data Matrix
Paper diameter	80mm
Paper off type	Tear off
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation
Gross weight	1.40 kg
Dimension	190(D) x 135(W) x 137(H)mm
Work	5~45℃, 20~80%RH
Storage	-40~55℃, ≤93%RH(40℃)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/Win 7/Win 8/Win 8.1/Linux/OPOS
Input	DC12V, 3A
Paper exists detection	Photoelectric sensor
Interface	USB
Memory	DRAM: 4M; FLASH: 4M
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM