

PXD61006

Thermal Receipt Printer

Key features

- Support QR CODE Printing
- 300mm/s high printing speed
- Serial+USB+Lan interface
- Support Linux, Win 10 system
- Built-in LED and beeper to avoid order missing



Windows 7



Windows 8



Windows 10



Linux



Specifications

Model	PXD61006
Printing method	Direct thermal
Printing speed	300mm/s
Paper width	79.5±0.5mm
Roll paper	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line 512 dots/line (80mm)
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code page	PC347 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、 PC863 (Canadian-French) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、 Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、Iranll、Latvian、Arabic、 PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2048K Bytes
Power supply	DC 24V ±2.5A
Cash drawer control	DC 24V ±1A
Interface	Serial+USB+Lan
Auto cutter	Partial
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature (0~45°C), humidity(10~80%)
Storage environment	Temperature (-10~60°C), humidity(10~90%)
Drivers	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/ Win 7/ Win 8/ Win 10/ Linux
Command	Compatible with ESC/POS
Gross weight	1.45 kg
Dimension	194.5×145×147mm (D×W×H)