

PXQ80010

Thermal Receipt Printer



Features

- Fast and versatile printing up to 300 mm per second
- Drop in paper loading and with auto cutter
- Horizontal or wall-hanging installation
- Queue function available

Technical specification

| | |
|------------------------|--|
| Printing method | Direct thermal |
| Printing speed | 300 mm/s |
| Paper width | 79.5 ± 0.5 mm |
| Printable area | 72 mm (adjustable by commands) |
| Maximum paper diameter | Φ 80 mm |
| Paper thickness | 0.06 - 0.08 mm |
| Column capacity | 576 dots / line 512 dots / line |
| Line space | 3.75 mm (changeable by commands) |
| Commands | Compatible with ESC/POS |
| Interface type | USB + Serial + LAN |
| Character size | ANK, Font A: 12×24 dots; Font B: 9×17 dots; simplified/traditional Chinese: 24x24 dots |
| Dimension | 195×140×142.5 mm (D×W×H) |
| Gross weight | 1.1 kg |
| Bar code | UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 |
| 2-dimension code | QR CODE / PDF417 |
| Code page | PC347 (Standard Europe), Katakana, PC850 (Multilingual) , PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), Pc858, IranII, Latvian, Arabic, PT151 (1251) |
| Cutter | Partial |
| Cutter life | 1.5 million cuts |
| Print head life | 100 km |
| Input buffer | 2048 Kbytes |
| NV Flash | 256 Kbytes |
| Power adaptor | AC 110V/220V, 50~60 Hz |
| Input voltage | DC 24V/2.5A |
| Cash drawer output | DC 24V/1A |
| Work environment | Temperature: 0~45 °C; humidity: 10~80 RH% |
| Storage environment | Temperature: -10~60 °C; humidity: 10~90 RH% |
| Operating system | Win XP / Win Vista / Win 7 / Win 8 / Win 8.1 / Win10 / Linux |