

PXR33009

Thermal Receipt Printer



Features

- 58mm/80mm/82.5mm paper width available
- Compact receipt printer, suitable for the smallest space. It can be placed horizontally or vertically.
- IAP function supports firmware update within 90s. Make printer maintained easily
- Reliable cutter with intelligent code to prevent cutter from cutter jammed
- Metallic frame mechanism

Technical specification

Printing method	Direct thermal
Printing speed	300 mm/s
Paper width	82.5 mm / 80 mm / 58 mm
Printable area	72 mm (adjustable by commands)
Maximum paper diameter	Φ 83 mm
Paper thickness	0.06 - 0.08 mm
Column capacity	576 dots / line (adjustable by commands)
Line space	3.75 mm (changeable by commands)
Commands	Compatible with ESC/POS
Interface type	USB+Serial+WLAN / USB+Serial+Bluetooth
Character size	ANK, Font A: 12×24 dots; Font B: 9×17 dots; simplified/traditional Chinese: 24x24 dots
Dimension	133×126×130 mm (D×W×H)
Gross weight	1.115 kg
Bar code	UPC-A / UPC-E / JA(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2-dimension code	QR CODE / PDF417
Code page	PC347 (Standard Europe), Katakana, PC850 (Multilingual) , PC860 (Portuguese), PC863(Canadian-French), PC865 (Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), Pc858, IranII, Latvian, Arabic, PT151 (1251)
Cutter	Partial
Cutter life	1.5 million cuts
Print head life	100 km
Input buffer	64 Kbytes
NV Flash	256 Kbytes
Power adaptor	AC 110V/220V, 50~60 Hz
Input voltage	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature: 0~45 °C; humidity: 10~80 RH%
Storage environment	Temperature: -10~60 °C; humidity: 10~90 RH%
Operating system	Win XP / Win Vista / Win 7 / Win 8 / Win 8.1 / Win10 / Linux