

VP220C2 Customer Display



- * Supports 11 command modes included EPSON etc.
- * Power supply from 5V to 24V to prevent any mindless use of improper power input.
- * 20-column x 2-line dot matrix in a wide viewing angle.
- * Easy connectivity to a wide range of POS products.
- * OPOS/JPOS driver is standard.

VP220C2 Customer Display



Specification

| | | |
|------------------|--|--|
| General | Display Method | LCD (Blue-White) |
| | Number of characters | 40 (20 columns x 2 lines) |
| | Brightness | 300~350 cd/m2 |
| | Character font | 8 x 16 dot matrix |
| | Character type | 95 Alphanumeric, 32 International Characters |
| | Character size | 4.86 (W) x 8.00 (H) mm |
| | Dot Size (X x Y) | 0.66 x 0.58 mm |
| | Download characters | 9 characters |
| | Panel Dimension | 168 (W) x 66.5 (D) x 28 (H) mm |
| | Pole Dimension | Per support length: 140(L) x 34.5(Dia)mm |
| | Base Dimension | 169.5 (W) x 98.5 (D) x 39 (H) mm |
| | Viewing Angle | Max. 90° |
| | Horizontal Rotation | Max. 355° |
| | Weight | Approx. 980 grams |
| Commands Mode | LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL | |
| Language Support | France, Germany, UK, Denmark-I, Sweden, Italy, Spain, Japan, Norway, Denmark-II, Slavonic, Russia, Portuguese, Canadian French, Nordic, Turkish, Greek, West European Latin, Simplified Chinese, traditional Chinese character | |
| Interface | RS-232(serial) / USB | |
| Connection | Baud rate | Direct connection 9600 or 19,200 bps |
| Reliability | MTBF | 30,000 hours |
| Power | Consumption | 5~24 VDC |
| Safety | EMC standards Safety standards | FCC, CE,ROHS |

Ardax Tech GmbH

Am Schiffbeker Berg 6, 22111 Hamburg, Tel. +49-40-46656240, Fax +49-40-466562455, Email: info@ardax-tech.eu