

# VP220V2 Customer Display



- \* Supports 11 command modes included EPSON etc.
- \* Power supply from 5V to 24V to prevent any mindless use of improper power input.
- \* 20-column x 2-line dot matrix in a wide viewing angle.
- \* Easy connectivity to a wide range of POS products.
- \* OPOS/JPOS driver is standard.

# VP220V2 Customer Display



## Specification

General	Display Method	Vacuum Fluorescent Display (Blue-green)
	Number of characters	40(20 columns x 2 lines)
	Brightness	500~1000 cd/m2
	Character font	5 x 7 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	<b>9.02(H) x 5.25(W) mm</b>
	Dot Size (X x Y)	<b>0.86 x 1.05mm</b>
	Download characters	9 characters
	Panel Dimension	<b>200(W) x 77.5(D) x31(H)mm</b>
	Pole Dimension	Per support length: 140(L) x 34.5(Dia)mm
	Base Dimension	169.5(W) x98.5(D) x39(H)mm
	Viewing Angle	Max. 90°
	Horizontal Rotation	Max. 355°
	Weight	Approx. 980 grams
Commands Mode	LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL	
Language Support	France, Germany, UK, Denmark-I, Sweden, Italy, Spain, Japan, Norway, Denmark-II, Slavonic, Russia, Portuguese, Canadian French, Nordic, Turkish, Greek, West European Latin	
Interface	RS-232(serial) / USB	
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5~24 VDC
Safety	EMC standards Safety standards	FCC, CE

### Ardax Tech GmbH

Am Schiffbeker Berg 6, 22111 Hamburg, Tel. +49-40-46656240, Fax +49-40-466562455, Email: info@ardax-tech.eu