

VP220V3 Customer Display



- * Supports 11 command modes included EPSON etc.
- * Power supply from 5V to 24V to prevent any mindless use of improper power input.
- * 20-column x 2-line dot matrix in a wide viewing angle.
- * Easy connectivity to a wide range of POS products.
- * OPOS/JPOS driver is standard.

VP220V3 Customer Display



Specification

General	Display Method	Vacuum Fluorescent Display (Blue-green)
	Number of characters	40(20 columns x 2 lines)
	Brightness	500~1000 cd/m2
	Character font	5 x 7 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	6.7(H) x 3.7(W) mm
	Dot Size (X x Y)	0.80 x 0.70mm
	Download characters	9 characters
	Panel Dimension	168(W) x 66.5(D) x 28(H)mm
	Pole Dimension	Per support length: 140(L) x 34.5(Dia)mm
	Base Dimension	169.5(W) x98.5(D) x39(H)mm
	Viewing Angle	Max. 90°
	Horizontal Rotation	Max. 355°
	Weight	Approx. 980 grams
Commands Mode	LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL	
Language Support	France, Germany, UK, Denmark-I, Sweden, Italy, Spain, Japan, Norway, Denmark-II, Slavonic, Russia, Portuguese, Canadian French, Nordic, Turkish, Greek, West European Latin	
Interface	RS-232(serial) / USB	
Connection	Baud rate	Direct connection 9600 or 19,200 bps
Reliability	MTBF	30,000 hours
Power	Consumption	5~24 VDC
Safety	EMC standards Safety standards	FCC, CE

Ardax Tech GmbH

Am Schiffbeker Berg 6, 22111 Hamburg, Tel. +49-40-46656240, Fax +49-40-466562455, Email: info@ardax-tech.eu