

# 15" POS LCD Display

## Product Features

- Stand base design for different viewing angles
- Touch version availability
- Card reader version availability
- Anti-reflection strengthen glass availability
- Cable management for neat installation (Touch version only)



## PA15 Specification

Specification \ Model		PA15
<b>DISPLAY</b>	Screen Size	15"
	Backlight	LED
	Aspect Ratio	4 : 3
	Max. Resolution	1024 x 768 (XGA)
	Viewable Size (HxV)	304,128 x 228,096 mm
	Pixel Pitch (HxV)	0,297 x 0,297
	Brightness (Typ.)	250 cd/m <sup>2</sup> none Touch, 200 cd/m <sup>2</sup> with Touch
	Contrast Ratio (Typ.)	700 : 1
	Viewing Angle (HxV)	150° / 140°
	Display Color	16.2M
Response Time (Tr/Tf) (Typ.)	2.3 / 5.7 ms	
<b>I/O INTERFACE</b>	Video Input	VGA / DVI (Optional)
	Audio Input	-
	Touch Interface	USB or RS232 interface
	USB	-
<b>ELECTRICAL</b>	Power Input	AC 100~240V, 50/60Hz
	Power Supply	DC12V / 4.0A
	Power Consumption	27W max. / Standby 2W max.
<b>GENERAL</b>	Operating Condition	Temp.: 0°C~40°C, Hum:20~80%
	Storage Condition	Temp.: -20°C~60°C, Hum:15~85%
	Dimension (WxHxD)	364 x 318 x 190 mm (without Card Reader) 405 x 318 x 190 mm (with Card Reader)
	Net Weight	5.2 Kg, 5,6Kg (with Card Reader)
	Regulations	FCC, CE, UL, BSMI, CCC
	Other	
<b>OPTION</b>	Touch Panel	Resistive (5Wires) / Cap. Touch and others
	Glass	Anti-Reflection Strengthen Glass
	Mounts	VESA standard 75x75 mm
	MSR	RS232 or USB MSR
	Cabinet Color	White or Black or Customized
	Other	2nd Display Bracket

\*Specifications subject to change without notice. V1.2

## Features and Options



Card Reader Version



Touch Screen



Anti-Reflection Strengthen Glass



Stand Base (0°~ 90°)



Stand Base (0°~ 90°)

## Function Panel



## Dimension

